



Imasco Minerals Inc.

## MATERIAL SAFETY DATA SHEET

**SECTION 1 - PRODUCT IDENTIFICATION AND USE**

PRODUCT IDENTIFIER: Imasco Acrylic Finish Coat Stucco

TRADE NAMES: FlexCoat (all textures and tints)  
 Perfector (all textures and tints)  
 Evolution (all textures and tints)

PRODUCT USE: Protective/Decorative Coatings

MFG'S NAME: Imasco Minerals Inc.

SUPPLIER'S NAME: Imasco Minerals Inc.

STREET: 19287 - 98A Avenue

STREET: 19287 - 98A Avenue

CITY: Surrey

PROVINCE: British Columbia

CITY: Surrey

PROVINCE: British Columbia

P.C.  
V4N 4C8EMERGENCY TEL.NO:  
8AM-5PM Weekdays  
(604) 888-3848P.C.  
V4N 4C8EMERGENCY TEL.NO:  
8AM-5PM Weekdays  
(604) 888-3848**SECTION 2 - HAZARDOUS INGREDIENTS/COMPOSITION INFORMATION**

INGREDIENTS	BY WEIGHT (%)	CAS NUMBER	LD <sub>50</sub> OF INGREDIENT	LC <sub>50</sub> OF INGREDIENT
Acrylic Latex	10 - 15	N/A	> 5 g/kg	> 5 g/kg
Titanium Dioxide	< 5	13463-67-7	N/A	N/A
Ethylene glycol	0.05-1.0	107-21-1	4 g/kg (Oral, Rat)	10 g/kg (Inhalation, Rat)

**SECTION 3 - PHYSICAL DATA**

PHYSICAL STATE: Liquid	ODOUR & APPEARANCE: Slight ammonia odour, viscous opaque white or coloured liquid			ODOUR THRESHOLD (ppm): No Data
VAPOUR PRESSURE (mm Hg): No Data	VAPOUR DENSITY (AIR=1): No Data	EVAPORATION RATE Equals Water	BOILING POINT (°C) 100 °C	FREEZING POINT (°C) 0 °C
pH: 7.5 - 9.0	SPECIFIC GRAVITY: 1.8 - 2.0	COEFF. WATER/OIL DIST. N/A		SOLUBILITY IN WATER: Miscible

**SECTION 4 - FIRE AND EXPLOSION DATA**FLAMMABILITY: YES \_ NO  IF YES, UNDER WHICH CONDITION:

MEANS OF EXTINCTION: N/A (non-flammable)

FLASHPOINT (°C) AND METHOD: N/A

UPPER FLAMMABLE LIMIT (% BY VOLUME): N/A

LOWER FLAMMABLE LIMIT (% BY VOLUME): N/A

AUTOIGNITION TEMPERATURE (°C): N/A

HAZARDOUS COMBUSTION PRODUCTS: N/A

EXPLOSION DATA: SENSITIVITY TO IMPACT: N/A

SENSITIVITY TO STATIC DISCHARGE: N/A

**SECTION 5 - REACTIVITY DATA**

PRODUCT IDENTIFIER: Imasco Acrylic Finish Coat Stucco

CHEMICAL STABILITY: YES  NO  IF NO, UNDER WHICH CONDITIONS:INCOMPATIBILITY WITH OTHER SUBSTANCES: YES  NO  IF SO WHICH ONES: Strong oxidizing and reducing agents

REACTIVITY, AND UNDER WHAT CONDITIONS: N/A

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen from burning of dried films.

HAZARDOUS POLYMERIZATION: Will not occur.

**SECTION 6 - TOXICOLOGICAL PROPERTIES**ROUTE OF ENTRY: SKIN CONTACT  SKIN ABSORPTION  EYE CONTACT  INHALATION  INGESTION 

EFFECTS OF ACUTE EXPOSURE TO PRODUCT: may cause headache, nausea, eye irritation and skin irritation.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: Contains ethylene glycol. Extreme exposures to mists, vapours or ingestion of large amounts may cause liver, kidney, red blood cell damage or central nervous system depression.

EXPOSURE LIMITS:  
No DataIRRITANCY OF PRODUCT:  
No DataSENSITIZATION TO PRODUCT:  
No DataCARCINOGENICITY:  
Not considered a  
carcinogen by IARC,  
NTP or OSHA.TERATOGENICITY:  
N/AREPRODUCTIVE TOXICITY:  
N/AMUTAGENICITY:  
N/ASYNERGISTIC PRODUCTS:  
No Data**SECTION 7 - PREVENTIVE MEASURES**

PERSONAL PROTECTIVE EQUIPMENT: Use all as specified

GLOVES (SPECIFY): Wear  
rubber glovesRESPIRATOR (SPECIFY): If product-use conditions  
create vapours or mists, or limited  
ventilation is available, a NIOSH  
approved organic vapour mask with a  
dust/mist pre-filter is recommendedEYE (SPECIFY): Goggles are  
recommendedFOOTWEAR (SPECIFY): Safety  
shoes are  
recommended

CLOTHING (SPECIFY): Long sleeved cover-alls

OTHER (SPECIFY): Wash hands and face  
thoroughly before eating or  
handling food.

ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS): General ventilation is normally adequate

LEAK AND SPILL PROCEDURE: Keep spectators away. Floor may be slippery. Contain spill with inert material or absorbent. Do not allow entering drain or waterways. Transfer liquid material to containers for recovery or disposal. Solid material can be placed in separate containers for disposal

WASTE DISPOSAL: Coagulate the liquid material with stepwise additions of ferric chloride and lime. Remove the clear supernatant liquid and flush to a chemical sewer. Landfill the solids and contaminated containment materials according to local, Provincial and Federal regulations

STORAGE REQUIREMENTS: Keep from freezing

SPECIAL SHIPPING INFORMATION: None

**SECTION 8 - FIRST AID MEASURES**

PRODUCT IDENTIFIER: Imasco Acrylic Finish Coat Stucco

SPECIFIC MEASURES:

Skin: Wash skin thoroughly with a mild soap and water. Consult a doctor if irritation develops.

Eyes: Flush eyes thoroughly with clean water. Consult a doctor if irritation develops.

Inhalation: Remove to fresh air. Apply artificial respiration if patient is not breathing. Get immediate medical attention.

Ingestion: If conscious, give victim 2 glasses of clean water and induce vomiting by placing a spoon or finger at the back of the throat. Do not give anything to an unconscious or convulsing person. Get immediate medical attention.

**SECTION 9 - PREPARATION DATE OF MSDS**

The information contained herein is based on data considered true and accurate to the best reasonably available information. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Imasco Minerals Inc. assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. This information is offered solely for informational purposes and is subject to your own independent investigation and verification.

PREPARED BY (GROUP, DEPARTMENT, ETC.):  
Technical Support Department

PHONE NUMBER:  
(604) 888-3848

DATE:  
January 21, 2016