



CUSTOM COLOURS FOR PREMIX, PREMIX 1000, ARTISAN PREMIX, FOGCOATS AND PORTLAND CEMENT MIXTURES

DESCRIPTION

MASCO CUSTOM COLOURS are available in dry powder form for use with IMASCO PREMIX FINISH COAT STUCCO (base white), IMASCO PREMIX1000 FINISH COAT STUCCO (base white), IMASCO ARTISAN PREMIX FINISH COAT STUCCO (base non-white), IMASCO FOGCOAT Bonding Cement Coating (base white), IMASCO ARTISAN FOGCOAT Bonding Cement Coating (base non-white) and code compliant or engineered mixtures using IMASCO STUCCO SANDS and Portland Cement or equivalent binders and additives.

PACKAGING:

Colours are sold by volume.
Case of 12.

COLOUR MIX INSTRUCTIONS:

IMASCO CUSTOM COLOURS (shown in our colour charts) are available in a convenient package for each of the attractive shades. The intensity of the colour will vary with the variety of texture chosen. Job site mixing shall follow instructions provided on the package and on Imasco data sheets.

SHADE	IMASCO DRY CUSTOM COLOUR	IMASCO FINISH COAT STUCCO
DARK	1 jar	1 bag
LIGHT	1 jar	6 bags

The maximum colour addition is 1 jar of IMASCO CUSTOM COLOURS per bag of IMASCO PREMIX. (equivalent to 6 jars in a 6 bag mix)

PREPARATION

Prior to application inspect the substrate to ensure that it has been constructed according to local building code standards. Substrates must be structurally sound and free from any loose materials, oil, mildew, or any form of deleterious material that could interfere with bond strength.

MIXING & APPLICATION

Follow instructions for product being pigmented.

HINTS FOR IMPROVING COLOUR CONSISTENCY

Colour indication is approximate. Variations in colour may occur due to weather, texture, job conditions and method of application. It is important to strictly follow the manufacturer's specifications and recommendations.

The following is a small list of hints for improving colour consistency. For more detailed information refer to Imasco's website or "Causes and Prevention of Colour Variation in Exterior Coloured Stucco" by Tom Geary (copies are available through Imasco).

- 1) Prior to application of the IMASCO PREMIX FINISH COAT STUCCO the substrate must be clean and free of deleterious materials. It should also be dampened with clean water, if required, to provide even suction.
- 2) For uniformity of texture and colour of IMASCO PREMIX FINISH COAT STUCCO, measurement of ingredients including amount of water must be accurate and successive batches shall be proportioned alike.
- 3) When using a coloured mix, the addition of water in the floating or trowelling application will disturb the colour and careful planning must be done to keep the working areas small enough to be completed without retempering with water.
- 4) IMASCO PREMIX FINISH COAT STUCCO remains in a separable state until fully set and additions of water or extensive troweling can cause segregation of ingredients resulting in uneven texture or colour distortion.
- 5) To reduce colour variations with spray applications a skim coat with steel trowel is recommended to ensure basecoat is covered. This prevents the basecoat from showing through in the texture.
- 6) If working on a large project, it is important to purchase the same colour batch number for the complete job. In the event there is a slight variation of colour between batches this will minimize potential colour variation problems.

IMASCO MINERALS INC.

19287-98A Avenue, Surrey, BC V4N 4C8
www.imascominerals.com

t: 604.888.3848
f: 604.888.5671
e: imasco@imascominerals.com

STORAGE

Keep in a dry, cool area protected from the weather. Protect from physical damage.

SAFETY PRECAUTIONS

IMASCO CUSTOM COLOURS can irritate the eyes and skin. Avoid contact with eyes or prolonged contact with skin. In case of skin contact wash thoroughly with water. Wear eye protection and non-toxic particle mask. Do not take internally. KEEP OUT OF REACH OF CHILDREN. In case of eye contact, flush with large amounts water for at least 15 minutes. Please refer to S.D.S. for additional information.

WARRANTY

IMASCO CUSTOM COLOURS are manufactured to strict quality standards using the highest quality ingredients. Imasco Minerals Inc. fully guarantees its products and will refund or replace any product found to be defective. Liability is limited to replacement or refund only and no other warranty is expressed or implied. For individual products, Imasco Minerals Inc. offers a 5 year material defect warranty. Please see written warranties for further details.

Imasco Minerals Inc. is unable to accept responsibility for job conditions, workmanship, climate, damages due to transport, improper design, engineering or construction, or non-performance of adjacent materials. IMASCO products are intended for use by qualified professionals and are to be applied in accordance with all manufacturers' specifications. IMASCO disclaims all, and assumes no, liability for on-site visits by any IMASCO representative. IMASCO also disclaims all warranties, expressed or implied, except written warranties issued by IMASCO in accordance with IMASCO's Warranty Programs.

If further information is required, please contact your IMASCO representative.

IMASCO MINERALS INC.

19287-98A Avenue, Surrey, BC V4N 4C8
www.imascominerals.com

t: 604.888.3848
f: 604.888.5671
e: imasco@imascominerals.com

21 March 2018